

DUO 175 XD

STEREO POWER AMPLIFIER



175 WATT AMPLIFIER FEATURING KRELL IBIAS TECHNOLOGY



**175 Watt Stereo Power Amplifier with Krell iBias
Class A Technology**

DUO 175 XD

175 WATT STEREO POWER AMPLIFIER

Krell iBias Class A amplifiers are the first to deliver the rich musicality of Class A amplifiers, the uncompromised dynamics of classic Krell amplifiers, with much greater efficiency than traditional Class A amplifiers.

DESIGN

Circuitry Highlights

Krell iBias Class A technology allows our latest amplifiers to run in full Class A mode to full power while minimizing heat generation.

All signal gain is realized in the current domain using discrete, proprietary, multiple-output current mirrors with extraordinary open loop linearity. There are no generic integrated circuits or op amps used anywhere.

The signal path is fully complementary and balanced. Independent complementary pre driver and driver stages for the positive and negative output transistors make the output stages extremely fast and linear.

Krell amplifiers are fully direct-coupled, with no capacitors in the audio signal path. This design gives the Krell amplifiers lower internal impedance, which allows firmer, more precise control of your speakers.

XD Explained

Krell's "XD" (Xtended Dynamics, Xtended Dimensionality, Xtended Detail) upgrade for the iBias amplifiers takes an already great sounding amplifier and raises its performance to the next level. "XD" is a classic example of Krell's continuous R&D efforts reaping benefits across multiple product lines. During the development of the K-300i Integrated Amplifier we discovered substantial sonic improvements by lowering the output impedance below traditional norms. So we applied this technique to our existing line of amplifiers and the improvement was so substantial that it required a unique designation, hence, "XD."

It was no simple matter to just lower the output impedance. This affects the amplifier's stability and transient response so each stage prior to the output stage had to be re-tuned to work optimally with the lower output impedance. This lower output impedance exerts more control over the speaker drivers and damps out unwanted vibrational modes, allowing a more accurate reproduction of the original signal.

SPECIFICATIONS

- 175 Watts into 8 Ohms
- 2 ea - Single-ended RCA and Balanced XLR Inputs
- 1 RJ45 Ethernet Port
- 1 12V Trigger Input
- WBT Speaker Binding Posts
- Optional Rack Mount Kit
- 17" (43.3cm) W x 7" (17.7cm) H x 21" (53.1cm) D
- Weight: 60lb (27kg)



Krell Industries, LLC. • 45 Connair Road • Orange, CT 06477-3697 USA
Tel: 203-298-4000 • Fax: 203-799-9796 • Sales Dept: 203-298-4010 • contact@krellonline.com • www.krellonline.com

All operational features, functions, specifications, and policies are subject to change without notice.

Krell® is a registered trademark of Krell Industries, LLC., and is restricted for use by Krell Industries LLC., its subsidiaries, and authorized agents. All other trademarks and trade names are registered to their respective companies. © 2018 by Krell Industries, LLC. All rights reserved.